



Kumnong engineering Inc.

www.kumnong.co.kr sales@kumnong.co.kr

031-756-7320

신상품안내

Series	Handheld W/ DMM Function		Education version	Bench series	
가격	700,000	900,000	450,000	700,000	800,000
Model No.	HDS1022M	HDS2062M	KDS5022	KDS6062	KDS6062
Display	Color 3.8 inch TFT LCD panel		Color 7.8 inch STN LCD panel	Color 8.0 inch STN LCD panel	Color 8.0 inch TFT LCD panel
Bandwidth	20MHz	60MHz	25MHz	60MHz	60MHz
Channels	2				
External Trigger Input	No	No	Available	Available	Available
Sample Rate on Each Channel	100Ms/S	250Ms/S	100Ms/S	250Ms/S	250Ms/S
Rising Time	17.5ns	17.5ns	17.5ns	5.8ns	5.8ns
Record Length	6K points per channel				
Vertical Resolution	8bits				
Vertical Sensitivity	5mV/div-5V/div				
DC Vertical Accuracy	±5%				
Max Input Voltage	400V	400V	300V	300V	300V
Input Coupling	AC/DC				
Input Impedance	1MΩ±2%				
Time Base Range	5ns-5s/div				
Time Base Accuracy	100ppm				
PC Interface	RS232/USB	RS232/USB	USB	USB	USB
Power Supply	100-240 V AC 50-60Hz				
Battery	6hr Li-ion rechargeable battery			Li-ion rechargeable battery (Not for Standard, Only for optional)	
Unit Dimension	180*113*40mm			350*157*120mm	
Unit Weight	690g			1kg	
Picture					